


# Cable assemblies

## Economical two pin accelerometer assemblies

The MIL-style IP 64 rated connector is an economical choice and suits applications in lighter industrial environments. Due to its size, the standard build does not feature an SKF logo and has limited options. The IP 64 connector/cable assembly is only available isolated; the shield is not connected to the sensor body.

Model number	Description	Compatible accelerometers
	<p><b>Standard build cables</b></p> 	<ul style="list-style-type: none"> <li>• CMSS 780A-IS</li> <li>• CMSS 780A-D2</li> <li>• CMSS 780C</li> <li>• CMSS 780C-M8</li> <li>• CMSS 786A-IS</li> <li>• CMSS 787A-IS</li> <li>• CMSS 787A-M8-IS</li> <li>• CMSS 793-CA</li> <li>• CMSS 793-EE</li> <li>• CMSS 793-FM</li> <li>• CMSS 793L</li> <li>• CMSS 793V</li> <li>• CMSS 793V-CA</li> <li>• CMSS 793V-EE</li> <li>• CMSS 793V-FM</li> <li>• CMSS 797-CA</li> <li>• CMSS 797-EE</li> <li>• CMSS 797L</li> <li>• CMSS 797L-FM</li> <li>• CMSS 797V</li> <li>• CMSS 2100</li> <li>• CMSS 2106</li> <li>• CMSS 2200</li> <li>• CMSS 2200-M8</li> <li>• CMSS 2207</li> </ul>
CMSS 932-64SBI-SY-5M	<p><b>Standard build, isolated</b></p> <p>Two wire, IP 64 connector, standard build, isolated, single shield, yellow cable, 5 m (16.4 ft.) length</p>	
CMSS 932-64SBI-SY-10M	<p>Two wire, IP 64 connector, standard build, isolated, single shield, yellow cable, 10 m (32.8 ft.) length</p>	
CMSS 932-64SBI-SY-10M	<p>Two wire, IP 64 connector, standard build, isolated, single shield, yellow cable, 20 m (65.6 ft.) length</p>	
	<p><b>Longer cable lengths are available upon request. Please contact your SKF Sales Representative.</b></p>	

# IP 64 rated cable/connector assembly – economical

## Ordering information

**CMSS 932** Two-wire twisted pair cable / two-pin connector assembly.

**CMSS 933** Three-wire twisted triad cable / three-pin connector assembly.

CMSS 93a-64SBI-Sb-ccc

### a: Wire

- 2 Two-wire twisted pair, two-pin connector
- 3 Three-wire twisted triad, three-pin connector

### 64: IP 64 connector (splash-proof)

### SB: Standard build

### I: Isolated

### S: Single shielded

### b: Jacket

- Y Yellow jacket
- B Blue jacket

### ccc: Length

- 5M Length: 5 meters (16.4 ft.)
- 10M Length: 10 m (32.8 ft.)
- 20M Length: 20 m (65.6 ft.)
- XXM Length: Specify XX meters, in 5 m increments