















SKF Cable assemblies 传感器电缆组件

Miscellaneous cable assemblies 杂项：传感器信号传输延长线组件、铠装电缆

Model number	Description	Compatible accelerometers
CMSS 30150000-16	 <p>BNC to sensor with two-pin MIL-C 5015 connector, coaxial connector cable, 4,88 m (16 ft.)</p>	<ul style="list-style-type: none"> All sensors with two-pin MIL-C 5015 connectors (CMSS 2100, CMSS 2200, CMSS 793, CMSS 797, etc.)
CMSS 30765400-10	 <p>BNC to Microdot 10-32 connector, coaxial connector cable, 3,05 m (10 ft.)</p>	<ul style="list-style-type: none"> CMSS 726 CMSS 732
CMSS R1-2-J3-25	 <p>BNC to Microdot 10-32 connector, high temperature interconnect cable, 7,62 m (25 ft.)</p>	
CMSS R1-J93-16	 <p>Coaxial, high temperature fluorine based polymer cable, Microdot 10-32 connector to blunt cut, 4,88 m (16 ft.)</p>	<ul style="list-style-type: none"> CMSS 726 CMSS 732
CMSS R1-J93-32	 <p>Coaxial, high temperature fluorine based polymer cable, Microdot 10-32 connector to blunt cut, 9,75 m (32 ft.)</p>	
CMSS 4850-015	 <p>Two pin, hermetically sealed connector with armored cable and trimmed wire, 4,57 m (15 ft.)</p>	<ul style="list-style-type: none"> CMSS 85-7 CMSS 85-9
CMSS 4850-050	 <p>Two pin, hermetically sealed connector with armored cable and trimmed wire, 15,24 m (50 ft.)</p>	
CMSS R19-J9T2PS-16	<p>Industrial cable assembly for special multi-parameter sensor, cables with PC06 connector</p>  <p>Shielded cable with PC06 connector, 4,88 m (16 ft.)</p>	<ul style="list-style-type: none"> CMSS 786M
CMSS R19-J9T2PS-32	 <p>Shielded cable with PC06 connector, 9,75 m (32 ft.)</p>	
CMSS R19-J9T2PS-64	 <p>Shielded cable with PC06 connector, 19,51 m (64 ft.)</p>	
CMSS R19SL-J9T2PS-16	<p>Industrial cable assembly for special multi-parameter sensor, cables with splash-proof connector</p>  <p>Shielded cable with splash-proof connector, 4,88 m (16 ft.)</p>	
CMSS R19SL-J9T2PS-32	 <p>Shielded cable with splash-proof connector, 9,75 m (32 ft.)</p>	
CMSS R19SL-J9T2PS-64	 <p>Shielded cable with splash-proof connector, 19,51 m (64 ft.)</p>	



技术咨询与报价

电话：18823303057 QQ:2104028976

Model number	Description	Compatible accelerometers
		
CMSS RM12-ST-J10-10	Cable connector assembly with M12 connector, IP 68, two-wire cable, isolated, single shield, grey, 3,05 m (10 ft.)	<ul style="list-style-type: none"> • CMSS 2100-M12
CMSS RM12-ST-J10-16	Cable connector assembly with M12 connector, IP 68, two-wire cable, isolated, single shield, grey, 4,88 m (16 ft.)	
CMSS RM12-ST-J10-32	Cable connector assembly with M12 connector, IP 68, two-wire cable, isolated, single shield, grey, 9,75 m (32 ft.)	
CMSS RM12-ST-J10-64	Cable connector assembly with M12 connector, IP 68, two-wire cable, isolated, single shield, grey, 19,51 m (64 ft.)	

Connectors and toolkits 电缆工具包

For on-site cable fabrication 现场电缆制作组装

Model number	Description
Connector packs for cables with a twist lock connector	
	
For CMSS 932 series	
CMSS 932-68TL-1	Connector pack for CMSS 932 series cable, two pin, IP 68, twist lock, isolated and non-isolated, single and double shield, quantity one
CMSS 932-68TL-10	Connector pack for CMSS 932 series cable, two pin, IP 68, twist lock, isolated and non-isolated, single and double shield, quantity 10
CMSS 932-68TL-50	Connector pack for CMSS 932 series cable, two pin, IP 68, twist lock, isolated and non-isolated, single and double shield, quantity 50
For CMSS 933 series	
CMSS 933-68TL-1	Connector pack for CMSS 933 series cable, three pin, IP 68, twist lock, isolated and non-isolated, single shield, quantity one
CMSS 933-68TL-10	Connector pack for CMSS 933 series cable, three pin, IP 68, twist lock, isolated and non-isolated, single shield, quantity 10
CMSS 933-68TL-50	Connector pack for CMSS 933 series cable, three pin, IP 68, twist lock, isolated and non-isolated, single shield, quantity 50
Connector packs for cables with a locking collar connector	
	
For CMSS 932 series	
CMSS 932-68LC-1	Connector pack for CMSS 932 series cable, two pin, IP 68, locking collar, isolated and non-isolated, single and double shield, quantity one
CMSS 932-68LC-10	Connector pack for CMSS 932 series cable, two pin, IP 68, locking collar, isolated and non-isolated, single and double shield, quantity 10
CMSS 932-68LC-50	Connector pack for CMSS 932 series cable, two pin, IP 68, locking collar, isolated and non-isolated, single and double shield, quantity 50
For CMSS 933 series	
CMSS 933-68LC-1	Connector pack for CMSS 933 series cable, three pin, IP 68, locking collar, isolated and non-isolated, single shield, quantity one
CMSS 933-68LC-10	Connector pack for CMSS 933 series cable, three pin, IP 68, locking collar, isolated and non-isolated, single shield, quantity 10
CMSS 933-68LC-50	Connector pack for CMSS 933 series cable, three pin, IP 68, locking collar, isolated and non-isolated, single shield, quantity 50